









SPIRAL WOUND CO-POLYMER CRUSH RESISTANT COMMERCIAL VACUUM HOSE

				UNLESS OTHERWISE SPECIFIED:		NAME	DATE	AMFLEX PLASTICS			
				TOLERANCES: FRACTIONAL±	DRAWN	TASC	9/7/09	7 HVII EE2X I EASI I ES			
					CHECKED			TITLE:			
					ENG APPR.						
					MFG APPR.				TUFF-FLEX 1	.50	.
				INTERPRET GEOMETRIC TOLERANCING PER:	Q.A.						
	PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF AMFLEX PLASTICS ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF AMFLEX PLASTICS IS PROHIBITED.				COMMENTS:						
				POLYOLEFIN BLEND				SIZE DV	VG. NO.	\	REV
		NEXT ASSY	USED ON	COLOR: BLACK					5TF150		
		APPLICATION		DO NOT SCALE DRAWING				SCALE: 2	2:1 WEIGHT:	WEIGHT: SHEET 1 C	
1		3		1)			1			